



Product Service

CERTIFICATE

No. Z1A 026000 0068 Rev. 00

Holder of Certificate: Deuter Sport GmbH

Daimlerstr. 23
86368 Gersthofen
GERMANY

Certification Mark:



Product: Backpack with integrated protector

Tested according to: PPP 63046D:2022
AfPS GS 2019:01 PAK

With this certificate, in its capacity as a notified GS body, TÜV SÜD Product Service GmbH issues the GS Mark to the named certificate holder for the declared product with the named model designation in accordance with section 20 ProdSG (German Product Safety Act). The product meets the safety and health requirements of section 20 (3) ProdSG. The manufacturer is reminded of their obligations in accordance with section 24 ProdSG. The certification marks shown above can be affixed on the product. It is not permitted to alter the certification marks in any way. In addition, the certificate holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the Testing, Certification, Validation and Verification Regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 028-713306580-1

Valid until: 2029-03-12

Date, 2024-03-14

(Thomas Michael Maier)

CERTIFICATE

No. Z1A 026000 0068 Rev. 00

Model(s): DEUTER Flyt 12 SL
DEUTER Flyt 14
DEUTER Flyt 20

Parameters:

Art.-No (Color Version)	Flyt 12 SL: 321102147010 & 321102136270 (graphite-black & lavender-almond) Flyt 14: 321112113740 & 321112147010 & 321112112030 (atlantic-ink & graphite-black & sprout-cactus) Flyt 20: 321132113740 & 321132147010 & 321132112030 (atlantic-ink & graphite-black & sprout-cactus)
Protector	Flyt 12 SL: Art.-No. LB-L (415 x 240 mm) Flyt 14, Flyt 20: Art.-No. LB-XL (450 x 255 mm)
Protector, Size	Flyt 12 SL: 415 x 240 mm Flyt 14, Flyt 20: 450 x 255 mm
Suitable for length of back	Flyt 12 SL: 38 – 48cm (S – L) Flyt 14, Flyt 20: 44 – 54cm (M – XL)
Residual Force +40°C	Max. < 12000 kN Ø < 9000 kN (Level 2)
Residual Force -20°C	Max. < 12000 kN Ø < 9000 kN (Level 2)
Residual Force RT	Max. < 12000 kN Ø < 9000 kN (Level 2)
Residual Force WET	Max. < 12000 kN Ø < 9000 kN (Level 2)